



“THE CLUTCH PEOPLE”

**PITTS ‘H’ SERIES CLUTCHES - STOCKED SIZES**

**BELT DRIVE**

<b>PART NO</b>	<b>MODEL</b>	<b>PUMP MOUNT</b>	<b>PUMP SHAFT</b>	<b>TORQUE*</b>
13233	H24V90 12V	SAE ‘A’ 2 bolt	3/4” SAE ‘A’ key	90 Lb.Ft
13817	H24V90 24V	SAE ‘A’ 2 bolt	3/4” SAE ‘A’ key	90 Lb.Ft
13667	H27V150 12V	SAE ‘A’ 2 bolt	5/8” SAE ‘A’ spline	150 Lb.Ft
14275	H27V15024V	SAE ‘A’ 2 bolt	5/8” SAE ‘A’ spline	150 Lb.Ft
13245	H28V200 12V	SAE ‘B’ 2/4 bolt	7/8” SAE ‘B’ spline	200 Lb.Ft
13654	H28V200 24V	SAE ‘B’ 2/4 bolt	7/8” SAE ‘B’ spline	200 Lb.Ft

**DIRECT DRIVE**

<b>PART NO</b>	<b>MODEL</b>	<b>PUMP MOUNT</b>	<b>PUMP SHAFT</b>	<b>TORQUE*</b>
13750	H24D90 12V	SAE ‘A’ 2 bolt	3/4” SAE ‘A’ key	90 Lb.Ft
14344	H24D90 24V	SAE ‘A’ 2 bolt	3/4” SAE ‘A’ key	90 Lb.Ft
14531	H27D150 12V	SAE ‘A’ 2 bolt	5/8” SAE ‘A’ spline	150 Lb.Ft
14532	H27D150 24V	SAE ‘A’ 2 bolt	5/8” SAE ‘A’ spline	150 Lb.Ft
13394	H28D200 12V	SAE ‘B’ 2/4 bolt	7/8” SAE ‘B’ spline	200 Lb.Ft
13914	H28D200 24V	SAE ‘B’ 2/4 bolt	7/8” SAE ‘B’ spline	200 Lb.Ft
13378	H36D400 12V	SAE ‘C’ 2/4 bolt	1-1/4” SAE ‘C’ spline	400 Lb.Ft
13856	H36D400 24V	SAE ‘C’ 2/4 bolt	1-1/4” SAE ‘C’ spline	400 Lb.Ft
13635	H49D1000 12V	SAE ‘C’ 2/4 bolt	1-1/4” SAE ‘C’ spline	1000 Lb.Ft
13902	H49D1000 24V	SAE ‘C’ 2/4 bolt	1-1/4” SAE ‘C’ spline	1000 Lb.Ft
14154-B	H55D1500 24V	SAE ‘D’ 2/4 bolt	1-3/4” SAE ‘D’ spline	1500 Lb.Ft

Brackets for H24&27, H28, H36&H49 and H55 also available.

\*Torque shown is maximum static torque, when an actual torque for the application a service factor must be added to this value. Please refer to Pitts Catalogue for service factors.